



## Avanza 5W-30 | Fully synthetic engine oil

### Property

- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- excellent cold starting characteristics
- good high temperature properties
- protects against premature ignition at low speed (LSPI → Low Speed Pre-Ignition)

### Application area

- especially suitable for Ford
- suitable for gasoline and diesel engines
- suitable for passenger cars and light commercial vehicles

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	5W-30
Color	-	brown
Viscosity @ 40°C	mm <sup>2</sup> /s	54
Viscosity @ 100°C	mm <sup>2</sup> /s	9.8
Viscosity index	-	169
Density @ 15°C	kg/l	0.851
Viscosity CCS @ -30°C	mPa·s	4010
Viscosity HTHS @ 150°C	mPa·s	2.9
Zinc content	ppm	1050
Sulphated ash	g/100g	1.11
Total base number	mg KOH/g	10.2
Pour Point	°C	-39
Flash Point	°C	230

### Available packaging

1 L bottle	4 L canister
Case 12 x 1 L bottles	Case 6 x 4 L canisters
50 kg drum (approx. 59 L)	175 kg drum (approx. 206 L)

### Specifications

ACEA A1/B1*, A5/B5
API SL*, SM*, SN*, SN Plus*, SP
Ford M2C913-A*, M2C913-B*, M2C913-C*, M2C913-D
Jaguar Land Rover STJLR.03.5003
Renault RN0700
VW VWC 53036

\* Additional Specifications