



## Avanza 10W-40 | Synthetic blend engine oil

### Property

- reduced emissions
- keeps the engine clean and protects against wear and corrosion
- good cold starting characteristics
- good high temperature properties
- protects against premature ignition at low speed (LSPI → Low Speed Pre-Ignition)

### Application area

- suitable for modern classics
- suitable for gasoline and diesel engines
- suitable for passenger cars and light commercial vehicles

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	10W-40
Color	-	brown
Viscosity @ 40°C	mm <sup>2</sup> /s	95.5
Viscosity @ 100°C	mm <sup>2</sup> /s	14.4
Viscosity index	-	156
Density @ 15°C	kg/l	0.86
Viscosity CCS @ -25°C	mPa·s	4210
Zinc content	ppm	1050
Pour Point	°C	-34
Flash Point	°C	210

### Available packaging

1 L bottle	4 L canister
Case 12 x 1 L bottles	Case 6 x 4 L canisters
54 kg drum (approx. 63 L)	180 kg drum (approx. 209 L)

### Specifications

ACEA A2/B2*, A3/B3*, A3/B4
API SL*, SM*, SN*, SN Plus*, SP
Fiat 9.55535-D2, G2
MB 229.1*, 229.3
PSA B71 2294, B71 2300
Renault RN0700, RN0710
Stellantis FPW9.55535/04
VW 500 00*, 501 01*, 502 00, 505 00

\* Additional Specifications