



Sensomatic | Fully synthetic automatic transmission fluid

Property

- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- lower fuel consumption thanks to lower viscosity
- excellent low temperature behaviour
- smooth gear changing at all temperatures and under load

Application area

- can be used where an ESSO LT 71141, Shell LA2634, Texaco 7045-E, 8072 B or N402 is recommended
- not recommended for continuously variable transmissions (CVT)
- suitable for automatic transmissions where a Mitsubishi Dia-Queen ATF J3, ATF PA, Shell ATF M-1375.4 or a ZF Lifeguardfluid 6, Lifeguardfluid 8 or Lifeguardfluid 9 is recommended
- for todays 6 to 10-speed automatic transmissions of several manufacturers

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Color	-	red
Viscosity @ 40°C	mm ² /s	27
Viscosity @ 100°C	mm ² /s	5.9
Viscosity index	-	172
Density @ 15°C	kg/l	0.845
Viscosity Brookfield @ -40°C	mPa·s	8220
Pour Point	°C	-46
Flash Point	°C	180

Available packaging

1 L bottle	Case 12 x 1 L bottles
50 kg drum (approx. 59 L)	175 kg drum (approx. 207 L)

Specifications

Aisin Warner AW-1
Allison C-3, C-4, TES-389
Caterpillar TO-2
Chrysler MS 7176 (ATF +3), 9602 (ATF +4)
Fiat 9.55550-AV1, AV2, AV3, AV4, AV5, AV6
Ford M2C924-A, Mercon LV (M2C938-A), Mercon SP
GM DEXRON-HP, II, IID, IIE, IIIF, IIIG, IIIH, VI
GM Type A Suffix A
Honda ATF DW-1, Type 3.0, Type 3.1, Z-1
Idemitsu K17
Isuzu Genuine
JASO 1A, 1A-LV
Mazda ATF-FZ, M-III, M-V
MB 236.2*, 236.5, 236.10, 236.11, 236.12, 236.14, 236.41, 236.82
MM MA1, SP-II, SP-III, SP-IV, SP-IV M, SP-IV M1, SP-IV RR
Nissan Matic D, Matic G, Matic J, Matic K, Matic S, Matic W
Saab 93 165 147
Subaru K0410Y0700
Toyota T-II, T-III, T-IV (JWS 3309), WS (JWS 3324/NWS 9638)
Volvo 97342 (AT102)
VW G 052 162, G 052 533, G 052 990, G 055 005, G 055 025, G 055 162, G 055 540, G 060 162
ZF TE-ML 11A, 11B

* Additional Specifications